



AVAILABLE OPTIONS



Product Description:

One piece die cast aluminum heatsink provides the most ideal heat dissipation, making the fixture cool to the touch

High performance optics provide maximum lighting solution to your needs



Optional 120V-277V button photocell available

Standard 6 KV surge protection included

IP 65 for both Optical and Electrical chamber

Product Description:

This compact but powerful flood light is a true innovation practically and aesthetically. With highly efficient LED engine and precise optical control, greater lighting performance adds the value to its exterior appearance. These LED lights have transformed the landscape lighting environment. Utilizing performance optics and long lasting driver, these landscape lights will last for years to come.

Features:

- LISTING**
- ▶UL and CUL listed for wet locations
- HOUSING**
- ▶Solid construction die-cast aluminum body
- FINISH**
- ▶UV stabilized powder coated finish
- OPTIONS**
- ▶Finish - Bronze. Color options with adder

Optional Kelvin color\* with adder.

Performance Data

Model NO.	System Watts	Beam Angle	Lumens	Lpw	B	U	G
LED-2375	69 W	70°×110°	8579 lm**	124 lm/W	3	1	1
LED-2390	92 W	80°×110°	11603 lm**	126 lm/W	3	2	1

Specification:

Example: LED-2375069UNV740-SF

Model No.	System Watts	Input Voltage	CRI	Color Temp	Option		Finish	Starting Temp
					Accessories	Mounting		
LED-2375	069=69W	UNV=120-277V	7=70+	30=3000 K	XS=10kv Surge PE=Photocontrol	SF=Slip Fitter U=U Bracket	BZ=Bronze	-40°C
LED-2390	092=92W			40=4000 K				
				50=5000 K				

Dimension:

