

Product Description:



Continuous poured gasket along with 6-8 acetal plastic latches to ensure a tight waterproof seal.

Die-cast IP66 conduit plugs.

Diffuse PC lens to provide efficient distribution of light.



Straps to prevent light engine from falling once installed.

Dual row PCBAs to provide efficiency and evenly distributed light output.

Optional internally mounted occupancy sensor

Quick release screws for easy install

Optional 8W Emergency Driver

CCT Tunable for LED-VL2

LED-VL4 with wattage and CCT tunable

Product Description:

The LED-VL is a linear vapor tight product designed to minimize cost while providing a fixture that is easy to install with high quality, performance, and is suitable where protection from dust and moisture are required.

Features:

LISTING

UL and CUL listed for wet locations

FINISH

UV stabilized power coated finish

LENS

High impact polycarbonate frosted lens

OPTIONS

Optional photo control with adder

Finish - Bronze / White

Performance Data

Model NO.	Nominal Watts**	Lumens**	Efficacy**
LED-VL2	23W	3423 lm*	154 lm/W*
LED-VL4	17W/26W/34W	5323 lm*	153 lm/W*
	26W/39W/54W	8175 lm*	155 lm/W*
	30W/45W/58W	8920 lm*	158 lm/W*

*Lumen and efficacy are based on highest wattage 5000K

Specification:

Example: LED-VL-2FT/LED-VL-4FT

Model No.	Nominal Watts**	Input Voltage	CRI	Color Temp	Sensor	Finish	Option
LED-VL2	23W	UNV=120-277VAC	7=70+	30=3000 K	BLANK=No sensor OS=Occupancy Sensor CFAO = CCT Tunable Controller	WH=White	EM = Emergency Driver C = Conduit
	17W/26W/34W			40= 4000 K			
LED-VL4	26W/39W/54W			50=5000 K			
	30W/45W/58W						