

Nomenclature

	D	F	C	036	3	S	XXX	C	A	A	X	X	X	X	X	X	X	A	*	
	1	2	3	4,5,6	7	8	9,10,11	12	13	14	15	16	17	18	19	20	21	22	23	24
Brand																				Revision Levels
D Daikin																				Major & Minor
Configuration																				
B Base Efficiency																				X No Options
F 2023 Standard Efficiency																				
R High Efficiency																				
Application																				PE Connection
C Cooling																				X No Options
G Gas/Electric																				B Single-point power connection for Power Exhaust
H Heat Pump																				
Nominal Cooling Capacity																				IAQ
036 3 Tons 090 7½ Tons 240 20 Tons																				X No Options
048 4 Tons 102 8½ Tons 300 25 Tons																				
060 5 Tons 120 10 Tons																				
072 6 Tons 150 12½ tons																				
Voltage																				Service Options
1 208-230/1/60 4 460/3/60																				X No Option
3 208-230/3/60 7 575/3/60																				A Powered convenience outlet
Supply Fan/Drive Type/Motor																				B Non-powered convenience outlet
D Direct Drive- Standard Static C Belt-Drive- High Static																				C Hinge Panels
B Belt-Drive- Standard Static S 2-speed Belt Drive- High Static																				D Hinged Panels and Powered convenience outlet
V 2-speed Belt Drive- Standard Static L Direct Drive-Medium Static																				E Hinged Panels and non-powered convenience outlet
W Direct Drive- High Static																				
Nominal Heating Capacity																				Electrical
Gas/Electric																				X No Options
A/C H/P Factory-Installed Electric Heat																				A Non-Fused Disconnect
045 45,000 BTU/h XXX No Heat XXX No Heat																				B Phase Monitor
060 60,000 BTU/h 005 5kW 022 20 kW																				C Thru-the-base connections
070 70,000 BTU/h 006 5kW 023 20 kW																				E Non-Fused Disconnect and Phase Monitor
080 80,000 BTU/h 010 10 kW 030 30 kW																				F Non-Fused Disconnect and Thru-the-base connectons
090 90,000 BTU/h 011 10 kW 031 30 kW																				H Phase Monitor and Thru-the-base connections
100 100,000 BTU/h 015 15 kW 032 30 kW																				L Non-Fused Disconnect, Thru-the-base connectons and Phase Monitor
115 115,000 BTU/h 016 15 kW 045 45kW																				
125 125,000 BTU/h 017 15 kW 046 45kW																				
130 130,000 BTU/h 018 18 kW 060 60kW																				
140 140,000 BTU/h 020 20 kW 075 75kW																				
150 150,000 BTU/h 021 20 kW																				
180 180,000 BTU/h																				
210 210,000 BTU/h																				
225 225,000 BTU/h																				
240 240,000 BTU/h																				
350 350,000 BTU/h																				
400 400,000 BTU/h																				
																				Economizer
																				X No Options
																				A Ultra Low-Leak Downflow Economizer w/ Enthalpy Sensor
																				B Low-Leak Downflow Economizer w/ Enthalpy Sensor
																				E Ultra Low-Leak Downflow Economizer for DDC controls w/ Enthalpy Sensorr
																				G Ultra Low-Leak Downflow Economizer w/ Dry Bulb Sensor
																				H Low-Leak Downflow Economizer w/ Dry Bulb Sensor
																				L Ultra Low-Leak Downflow Economizer for DDC controls w/ Dry Bulb Sensor
																				N Low-Leak Downflow Economizer for DDC controls w/ Enthalpy Sensor
																				P Low-Leak Downflow Economizer for DDC controls w/ Dry Bulb Sensor
Refrigeration Systems																				Coils, Hail guard
A Single stage cooling modes																				X No Options
C Two stage cooling modes																				A E-coat outdoor
F Two stage cooling modes with Hot Gas Reheat and Low-ambient control																				C Hail Guard
																				D E-coat outdoor w/ Hail Guard
Heat Exchanger																				Sensors
X No options																				X No Options
A Standard Aluminized Exchanger																				A RA Smoke Detector
S Stainless Steel Exchanger																				B SA Smoke Detector
U Ultra Low Nox Stainless Steel Exchanger																				C RA & SA Smoke Detector
Controls																				
A Electro-mechanical controls																				
B DDC w/ BACnet interface																				

AC Stocking Models	
New Daikin 3-6 Ton Direct Drive	
MODEL NUMBER	CODESTRING
DFC0361D000001S	DFC0361DXXXXAXXXXXXXXXXX
DFC0363D0000001S	DFC0363DXXXXAXXXXXXXXXXX
DFC0364D0000001S	DFC0364DXXXXAXXXXXXXXXXX
DFC0367D0000001S	DFC0367DXXXXAXXXXXXXXXXX
DFC0481D000001S	DFC0481DXXXXAXXXXXXXXXXX
DFC0483D0000001S	DFC0483DXXXXAXXXXXXXXXXX
DFC0484D0000001S	DFC0484DXXXXAXXXXXXXXXXX
DFC0487D0000001S	DFC0487DXXXXAXXXXXXXXXXX
DFC0601D0000001S	DFC0601DXXXXAXXXXXXXXXXX
DFC0603D0000001S	DFC0603DXXXXAXXXXXXXXXXX
DFC0604D0000001S	DFC0604DXXXXAXXXXXXXXXXX
DFC0607D0000001S	DFC0607DXXXXAXXXXXXXXXXX
DFC0723D000001S	DFC0723DXXXXCAXXXXXXXXXXX
DFC0724D000001S	DFC0724DXXXXCAXXXXXXXXXXX
DFC0727D000001S	DFC0727DXXXXCAXXXXXXXXXXX
DFC0723W000001F	DFC0723WXXXXCAXXXXXXXXXXX
DFC0724W000001F	DFC0724WXXXXCAXXXXXXXXXXX
DFC0727W000001F	DFC0727WXXXXCAXXXXXXXXXXX

Model	DFC0361D000001S	DFC0363D000001S	DFC0364D000001S	DFC0367D000001S
COOLING CAPACITY				
Total, BTU/h	35,000	35,000	35,000	35,000
SEER / EER	N/A	14.0 / 11.5	14.0 / 11.5	14.0 / 11.5
SEER2 / EER2	13.4 / 11.0	13.4 / 11.0	13.4 / 11.0	13.4 / 11.0
AHRI Reference #	208120664	208120661	208120662	208120663
EVAPORATOR MOTOR / RTPF (ROUND TUBE PLATE FIN)				
Motor Type	Direct Drive	Direct Drive	Direct Drive	Direct Drive
External Static Pressure (ESP)	Standard	Standard	Standard	Standard
Wheel Dia. X Width	12 x 11	12 x 11	12 x 11	12 x 11
Indoor Nominal CFM	1160	1160	1160	1160
RPM	1200/VAR	1200/VAR	300-1500	300-1500
Indoor Horsepower	3/4	3/4	1.2	1.2
Filter Size (in)	20 X 25 X 2 (2)	20 X 25 X 2 (2)	20 X 25 X 2 (2)	20 X 25 X 2 (2)
Drain Size (NPT)	3/4	3/4	3/4	3/4
R-410A Refrigerant Charge (oz.)	52	52	52	52
Evaporator Coil Face Area (ft ²)	6.41	6.41	6.41	6.41
Rows Deep / Fins per Inch	2 / 16	2 / 16	2 / 16	2 / 16
CONDENSER FAN / MCHX (MICROCHANNEL HEAT EXCHANGER)				
Quantity of Condenser Fan Motors	1	1	1	1
RPM (High/Low stage)	810	810	810	810
Outdoor Horsepower	1/6	1/6	1/6	1/6
Fan Diameter / # Fan Blades	22 / 3	22 / 3	22 / 3	22 / 3
Face Area (ft ²)	12.3	12.3	12.3	12.3
Rows Deep / Fins per Inch	1 / 23	1 / 23	1 / 23	1 / 23
COMPRESSOR (ALL SINGLE-STAGE)				
Quantity / Type / Stages	1 / Scroll / 1	1 / Scroll / 1	1 / Scroll / 1	1 / Scroll / 1
Compressor RLA / LRA	16.7 / 79	10.4 / 73	5.8 / 38	3.8 / 36.5
ELECTRICAL DATA				
Voltage-Phase-Frequency	208/230-1-60	208/230-3-60	460-3-60	575-3-60
Indoor Blower FLA	5.7	5.7	2.5	2
Max External Static (In. W.C.)	0.8	0.8	0.8	0.8
Outdoor Fan FLA	0.95	0.95	0.48	0.39
Min. Circuit Ampacity ¹	27.5/27.5	19.7/19.7	10.2	7.12
Max. Overcurrent Protection (A) ²	40/40	30/30	15	15
Power Supply Conduit Hole Dia. (in)	1.125	1.125	1.125	1.125
Low-Voltage Conduit Hole Dia. (in)	0.5	0.5	0.5	0.5
OPERATING WEIGHT (LBS.)				
Operating Weight (lbs)	484	482	490	490
SHIPPING WEIGHT (LBS.)				
Ship Weight (lbs)	554	552	560	560

¹ Wire size should be determined in accordance with National Electrical Codes. Extensive wire runs will require larger wire sizes.

² May use fuses or HACR-type circuit breakers of the same size as noted.

Note: Always check the S&R plate for electrical data on the unit being installed.