

Model name (Combination unit)			RXYQ312AAAYDA	RXYQ336AAAYDA
Model name (Independent unit)			RXYQ144AAAYDA RXYQ168AAAYDA	RXYQ168AAAYDA RXYQ168AAAYDA
Power supply			3 phase, 460 V, 60 Hz	3 phase, 460 V, 60 Hz
★1 Cooling capacity	Nominal	Btu/h (kW)	312,000 (91.4)	336,000 (98.5)
	Rated		296,000 (86.7)	320,000 (93.8)
★2 Heating capacity	Nominal	Btu/h (kW)	351,000 (103)	378,000 (111)
	Rated		320,000 (93.8)	338,000 (99.1)
Casing color			Ivory white (5Y7.5/1)	Ivory white (5Y7.5/1)
Dimensions: (H × W × D)		in. (mm)	65-3/8 × 48-13/16 × 30-1/8 + 65-3/8 × 48-13/16 × 30-1/8 (1,660 × 1,240 × 765 + 1,660 × 1,240 × 765)	65-3/8 × 48-13/16 × 30-1/8 + 65-3/8 × 48-13/16 × 30-1/8 (1,660 × 1,240 × 765 + 1,660 × 1,240 × 765)
Heat exchanger			Cross fin coil	Cross fin coil
Compressor	Type		Hermetically sealed scroll type	Hermetically sealed scroll type
	Volume	m <sup>3</sup> /h	(11.6 + 17.6) + (13.8 + 21)	(13.8 + 21) + (13.8 + 21)
	Number of revolutions	r/min	(5,496 + 5,196) + (6,504 + 6,204)	(6,504 + 6,204) + (6,504 + 6,204)
	Motor output × Number of units	kW	(3.36 + 5.41) × 1 + (3.97 + 6.46) × 1	(3.97 + 6.46) × 1 + (3.97 + 6.46) × 1
	Starting method		Soft start	Soft start
Fan	Type		Propeller fan	Propeller fan
	Motor output × Number of units	kW	0.65 × 2 + 0.65 × 2	0.65 × 2 + 0.65 × 2
	Airflow rate	cfm (m <sup>3</sup> /min)	9,935 (281.3) + 9,935 (281.3)	9,935 (281.3) + 9,935 (281.3)
	Drive		Direct drive	Direct drive
Connecting pipes	Liquid pipe	in. (mm)	ϕ 3/4 (19.1) C1220T (brazing connection)	ϕ 3/4 (19.1) C1220T (brazing connection)
	Gas pipe	in. (mm)	ϕ 1-3/8 (34.9) C1220T (brazing connection)	ϕ 1-3/8 (34.9) C1220T (brazing connection)
Weight		lbs (kg)	761 (345) + 761 (345)	761 (345) + 761 (345)
Sound pressure level (Reference data)		dB(A)	69	69
Sound power level (Reference data)		dB	89	89
Safety devices			High pressure switch, Fan driver overload protector, Overcurrent fuse, Inverter overload protector, Leak detecting device	High pressure switch, Fan driver overload protector, Overcurrent fuse, Inverter overload protector, Leak detecting device
Defrost method			Deicer	Deicer
Capacity control		%	1-100	1-100
Refrigerant	Refrigerant name		R-410A	R-410A
	Charge	lbs (kg)	25.8 (11.7) + 25.8 (11.7)	25.8 (11.7) + 25.8 (11.7)
	Control		Electronic expansion valve	Electronic expansion valve
Standard accessories			Installation manual, Operation manual, Connection pipes, Clamps	Installation manual, Operation manual, Connection pipes, Clamps
Drawing No.			4D144731	4D144732

**Notes:**

- ★1. Indoor temp.: 80°FDB (26.7°CDB), 67°FWB (19.4°CWB) / Outdoor temp.: 95°FDB (35.0°CDB) / Rated capacity is certified under AHRI standard 1230.  
★2. Indoor temp.: 70°FDB (21.1°CDB) / Outdoor temp.: 47°FDB (8.3°CDB), 43°FWB (6.1°CWB) / Rated capacity is certified under AHRI standard 1230.